

# bizhub C258

- □ Up to 25 pages per minute

# Functionality



- Colour
- Black & white PCL/PS Local/Network



- Colour
- Black & white Scan-to-eMail
- Scan-to-Me
- Scan-to-Home
- Scan-to-DPWS
- Scan-to-FTP Scan-to-Box - Scan-to-USB
- Scan-to-WebDAV





- Colour - Black & white





- PC-Fax - i-Fax - IP-Fax

- Super G3 Fax





- Sharing Box-to-Box

- Reprint










# Technology

Emperon™ – print controller	Easily compatible with different users and IT environments through Konica Minolta's unified print technology	
Simitri® HD – polymerised toner	Delivers high print quality and yet ensures reduced print spending as well as lower environmental impact	
OpenAPI – solution platform	Server-based applications provide efficient workflows for the entire MFP fleet	
i-Option – special feature	Offers extended scope and advanced MFP functionality in line with individual requirements	
CSRC – remote service	Keeps productivity up with online monitoring of devices and consumables through the Konica Minolta service	
IWS – panel customisation	Improved user-device interaction and enhanced productivity through full MFP panel customisation	

## Option diagram



## Finishing functionalities













mixmedia





insertion,

report











# Descriptions

bizhub C258	A3 multifunctional with 25 ppm b/w and colour.
	Standard Emperon™ print controller with PCL 6c,
	PostScript 3, PDF 1.7 and XPS support. Paper capacity
	of 500 + 500 sheets and 150-sheet manual bypass.
	Media from A6 to SRA3, 1.2 m banner and 52 – 300
	gsm. 2 GB memory, 250 GB hard disk and Gigabit
	Ethernet standard
DF-629 Document feeder	Reversing automatic document feeder.
DI 023 Document lecael	capacity 100 originals
DF-704 Document feeder	Dualscan automatic document feeder.
DF-704 Document leedel	capacity 100 originals
OC-511 Original cover	Cover instead of ADF
	OTTO MOLOGIC OTTO
PC-110 1 x Universal tray	A5–A3, 500 sheets, 52–256 gsm
PC-210 2 x Universal tray	A5-A3, 2 x 500 sheets, 52-256 gsm
PC-410 Large capacity tray	A4, 2,500 sheets, 52–256 gsm
DK-510 Copier desk	Provides storage space for print media and other
	materials
LU-302 Large capacity tray	A4, 3,000 sheets, 52–256 gsm
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/4 hole punching, autoswitching
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534SD Booklet finisher	50-sheets staple finisher, 20-sheets booklet finisher,
	2,300 sheets max. output
RU-513 Relay unit	For FS-534/SD installation
for FS-534/SD	
PK-520 Punch kit	2/4 hole punching, autoswitching
for FS-534/SD	
JS-506 Job separator	Separation for fax output etc.
KP-101 10-Key pad	For use instead of touchscreen

WT FOC Warding table	A. Manadiantian davian alanamant
WT-506 Working table	Authentication device placement
FK-514 Fax board	Super G3 fax, digital fax functionality
IC-416 Fiery controller	Professional colour print controller
VI-508 Interface kit for IC-416	,
KH-102 Keyboard holder	To place USB keyboard
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
AU-102 Biometric	Finger vein scanner
authentication	
SC-508 Security kit	Copy Guard function (2 kits required if DF-704 is installed)
HD-524 Hard disk mirroring	Back-up HDD
BT-C1e Banner tray	Multipage banner feeding
LK-102v3 PDF enhancements	PDF/A (1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX, PDF/A (1a)
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document	Generates various file formats incl. DOCX, XLSX and
converter pack	PDF/A
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LK-115v2 TPM activation	Trusted Platform Module for protection of data
	encryption and decryption
UK-211 Upgrade kit	2 GB memory extension for upgrades
UK-212 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
SX-BR-4600 Wireless LAN	Wireless LAN to network connector
MK-745 Attachment kit	Installation kit for CU-101
CU-101 Air cleaning unit	Improving indoor air quality by reduced emissions
•	

# **✓** Technical specifications

## SYSTEM SPECIFICATIONS

SYSTEM SPECIFICATION	JNS
System memory	2,048 MB (standard)
System hard disk	250 GB (standard)
Interface	10-Base-T/100-Base-T/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n (optional)
Network protocols	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk);
	SMB; LPD; IPP; SNMP; HTTP
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic document	Up to 100 originals; A6-A3; 35-163 gsm
feeder (optional)	RADF or Dualscan ADF available
Printable paper size	A6-SRA3, customised paper sizes;
	banner paper max. 1,200 x 297 mm
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets
	Max.: 6,650 sheets
Tray 1	500 sheets, A5–A3, 52–256 gsm
Tray 2	500 sheets, A5–SRA3, 52–256 gsm
Tray 3 (optional)	1 x 500 sheets, A5–A3, 52–256 gsm
Tray 4 (optional)	2 x 500 sheets, A5–A3, 52–256 gsm
Large capacity tray	2,500 sheets, A4, 52–256 gsm
(optional)	
Large capacity tray	3,000 sheets, A4, 52–256 gsm
LU-302 (optional)	
Manual bypass	150 sheets, A6-SRA3, custom sizes, banner, 60-300 gsm
Automatic duplexing	A5-SRA3; 52-256 gsm
Finishing modes	Offset; group; sort; staple; punch; centre-fold; letter fold;
(optional)	booklet
Output capacity	Max.: 3,300 sheets
(with finisher)	
Output capacity	Max.: 250 sheets
(without finisher)	
Stapling	Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	
Letter fold	Up to 3 sheets
Letter fold capacity	Max.: 30 sheets (tray); unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray); unlimited
Copy/print volume	Rec.: 13,000 pages
(monthly)	Max.1: 80,000 pages
Toner lifetime	Black 28,000 pages; CMY 26,000 pages

Imaging unit lifetime	Black 90,000 pages/600,000 pages (Drum/Developer)
	CMY 55,000 pages/600,000 pages (Drum/Developer)
Power consumption	220-240 V / 50/60 Hz Less than 1.5 kW (system)
System dimensions	615 x 685 x 771 mm (excl. ADF and lower paper tray unit)
(W x D x H)	
System weight	Approx. 85 kg
COPIER SPECIFICATION	ONS
Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD polymerised toner
Copy/print speed A4	Up to 25 ppm
(mono/colour)	
Copy/print speed A3	Up to 15 ppm
(mono/colour)	
Autoduplex speed A4	Up to 25 ppm
(mono/colour)	
1st copy out time	6.1 sec.
(mono/colour)	7.5 sec.
Warm-up time	Approx. 20 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	A5-A3
Magnification	25-400% in 0.1% steps; auto-zooming
Copy functions	Chapter; cover and page insertion; proof copy (print and
	screen); adjustment test print; digital art functions; job set-
	ting memory; poster mode; image repeat; overlay (optional);
	stamping; copy protection

 $<sup>^{\</sup>mbox{\scriptsize 1}}$  If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed <sup>2</sup> Warm-up time may vary depending on the operating environment and usage



DDIN	TED	CDEC	ZIUVIL

PRINTER SPECIFICATIONS		
1,800 x 600 dpi; 1,200 x 1,200 dpi		
PCL 6 (XL 3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS		
Windows VISTA (32/64), Windows 7 (32/64)		
Windows 8 (32/64), Windows 10 (32/64),		
Windows Server 2008 (32/64), Windows Server 2008 R2		
Windows Server 2012, Windows Server 2012 R2		
Macintosh OS X 10.x, Unix, Linux, Citrix		
80 PCL Latin; 137 PostScript 3 Emulation Latin		
Direct print of PCL, PS, TIFF, XPS, PDF (v1.7),		
encrypted PDF files and OOXML (DOCX, XLSX, PPTX);		
mixmedia and mixplex; "Easy Set" job programming;		
overlay; watermark; copy protection; carbon copy print		
AirPrint (iOS), Mopria (Android), Google Cloud Print (optional),		
WiFi Direct (optional), Konica Minolta Print Service (Android),		
PageScope Mobile (iOS & Android); NFC Authentication and		
Pairing (Android)		

#### PRINTER SPECIFICATIONS (OPTIONAL)

I THINTER OF EOIL TOA	HONS (OF HONAL)
Print controller	Embedded Fiery IC-416
Controller CPU	Intel Pentium @ 2.9 GHz
Memory/HDD	2 GB/500 GB
Page description	Adobe PostScript 3 (CPSI 3020)
language	PCL 6/5
Operating systems	Windows VISTA (32/64), Windows 7 (32/64),
	Windows 8 (32/64), Windows 10 (32/64),
	Windows Server 2008 (32/64), Windows Server 2008 R2,
	Windows Server 2012, Windows Server 2012 R2
	Macintosh OS 9.x/10.x

#### SCANNER SPECIFICATIONS

SOANNEN SI ESIN ISAN ISNO		
Scan speed	Up to 160 ipm (with optional DF-704)	
(mono/colour)		
Scan resolution	Max.: 600 x 600 dpi	
Scan modes	Scan-to-eMail (Scan-to-Me), Scan-to-SMB (Scan-to-Home)	
	Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV	
	Scan-to-DPWS, Network TWAIN scan	
File formats	JPEG; TIFF; PDF; PDF/A 1a and 1b (optional); compact PDF;	
	encrypted PDF; searchable PDF (optional); XPS; compact XPS;	
	PPTX; searchable DOCX/XLSX/PPTX (optional)	
Scan destinations	2,100 (single + group); LDAP support	
Scan functions	Annotation (text/time/date) for PDF; up to 400 job programs;	
	real-time scan preview	

### FAX SPECIFICATIONS

TAX SPECIFICATIONS	
Fax standard	Super G3 (optional)
Fax transmission	Analogue
	i-Fax
	Colour i-Fax (RFC3949-C)
	IP-Fax
Fax resolution	Max.: 600 x 600 dpi (ultra-fine)
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Polling; time shift; PC-Fax; receipt to confidential box;
	Receipt to e-mail/FTP/SMB: up to 400 job programs

## USER BOX SPECIFICATIONS

Max. storable	Up to 3,000 documents or 10,000 pages	
documents		
Type of user boxes	Public	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure print	
	Encrypted PDF print	
	Fax receipt	
	Fax polling	
User box functionality	Reprint; combination	
	Download	
	Sending (e-mail/FTP/SMB and Fax)	
	Copy box to box	
CVCTEM FEATURES		

#### SYSTEM FEATURES

SYSTEM FEATURES	
Security	ISO15408/IEEE 2600.2 compliant (in evaluation);
	IP filtering and port blocking;
	SSL2; SSL3 and TSL1.0 network communication;
	IPsec support; IEEE 802.1x support; user authentication;
	Authentication log; secure print;
	Hard disk overwrite (8 standard types);
	Hard disk data encryption (AES 256);
	Hard disk mirroring (optional); Memory data auto deletion;
	Confidential fax receipt; Print user data encryption;
	copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts; Active Directory support
	(user name + password + e-mail + smb folder)
	User function access definition
	Biometric authentication (finger vein scanner) optional
	ID card authentication (ID card reader) optional
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility

- All specifications refer to A4-size paper of 80 gsm quality.

Log Management Utility

- All specifications refer to A4-size paper of 80 gsm quarry.
   The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
   The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media
- type, continuous or intermittent printing, ambient temperature and humidity. Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

  Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.































